



**SCREWS TO BE PACKED SEPERATELY
IN PLASTIC POUCH WITH LABEL & PUT INTO
WELDON BORE & THEN SEAL THE HOLDER WITH COVER**


CUSTOMER APPROVAL REQUIRED

DATE _____

FOR QUOTATION PURPOSE ONLY

ALL SILVER LOOK

B-B (1 : 1.2)



Label :
2002366.2501
WELDON-AUFNAHME MIT KK
WELD.HOLDER COOL.CHANNEL
DIN69871 SK50 ADB
Wk 25 mm x 100 mm
G2.5 / 25000

NOTE :

BALANCING 2.5G AT 25000 RPM

WEIGHT : 4.2 kg

MARKING : DIN 69871 AD/B SK50 WK25H100
G2.5 25000 U/MIN

DIN 9137 AD/B
(SK 50 FTC)

100

80.90

25±0.5

24-1

54

64

25 H5

45

65

45°

GS-M18X2X20 DIN 1835-B

			μ m	0.012	0.025	0.05	0.1	0.2	0.4	0.8	1.6	3.2	6.3	12.5	25	50
			GRADES	N1	N2	N3	N4	N5	N6	N7	N8	N9	N10	N11	N12	
			SYMBOLS	▽▽▽▽				▽▽▽		▽▽			▽		~	
TOLERANCE			MATERIALS:				2017		NAME		DATE		2002366.2501			
FREE DIMENSIONS			16MnCr5				DRAWN		ELA		03/05					
TOLERANCE																
Dimms.		Dia	Length			CHECKED		RVL		03/05						
0.5 to 3		± 0.05	± 0.10			APPROVED				-						
3 to 6		± 0.10	± 0.15			SCALE : NTS		QTY. :								
6 to 30		± 0.15	± 0.20	PART NAME: SK50EK25100FWW						DRAWING No.				REV		
30 to 120		± 0.20	± 0.25							FWS509H-EKH25100						
120 to 500		± 0.30	± 0.50													