




For Customer Approval



**MARKING : DIN 69893 A HSK100A WE08H130
G2.5 25000 U/MIN**



			γ m	$0.012 \sqrt{\quad}$	$0.025 \sqrt{\quad}$	$0.05 \sqrt{\quad}$	$0.1 \sqrt{\quad}$	$0.2 \sqrt{\quad}$	$0.4 \sqrt{\quad}$	$0.8 \sqrt{\quad}$	$1.6 \sqrt{\quad}$	$3.2 \sqrt{\quad}$	$6.3 \sqrt{\quad}$	$12.5 \sqrt{\quad}$	$25 \sqrt{\quad}$	$50 \sqrt{\quad}$		
			GRADES	N1	N2	N3	N4	N5	N6	N7	N8	N9	N10	N11	N12			
			SYMBOLS															
TOLERANCE			MATERIALS: 16MnCr5															
FREE DIMENSIONS																		
TOLERANCE			2015		NAME		DATE		2002378.0805									
			DRAWN		MHP		22/08											
Dimms. Dia Length					CHECKED		RVL										22/08	
0.5 to 3 ± 0.05 ± 0.10					APPROVED													
3 to 6 ± 0.10 ± 0.15					SCALE : NTS		QTY. :											
6 to 30 ± 0.15 ± 0.20			PART NAME: HSKA100EM08130WW							DRAWING No. FWA100H-EMH08130							REV. 00	
30 to 120 ± 0.20 ± 0.25																		
120 to 500 ± 0.30 ± 0.50																		