





**MARKING : DIN69893 A HSK100A SFHC12H120
G2,5/25000 U/MIN**

Rev.No.	Ch.Let	Alterations	Date	Sign.	Appd.



For Customer Approval

SCREWS TO BE PACKED SEPERATELY
IN PLASTIC POUCH WITH LABEL & PUT INTO
BORE & THEN SEAL THE
HOLDER WITH COVER
LABEL FOR PLASTIC BAGS:
Verschlusschraube
Grub Screw
M3 X 5mm X1.5mm



Notes	
Balancing Value	G2.5 @25000RPM
Approx Weight	2.4Kg

				μm	0.012	0.025	0.05	0.1	0.2	0.4	0.8	1.6	3.2	6.3	12.5	25	50	
				GRADES	N1	N2	N3	N4	N5	N6	N7	N8	N9	N10	N11	N12		
				SYMBOLS														
TOLERANCE FREE DIMENSIONS TOLERANCE				MATERIALS: HDS	2022		NAME		DATE		2002387.1201							
				DRAWN		SVR		16/04										
Dimms. Dia Length								CHECKED RVL		16/04								
0.5 to 3 ±0.05 ±0.10				APPROVED														
3 to 6 ±0.10 ±0.15				SCALE : NTS		QTY. :												
6 to 30 ±0.15 ±0.20				PART NAME: HSKA100SFK12120WW						DRAWING No. F1A100H-SFK12120						REV. 00		
30 to 120 ±0.20 ±0.25																		
120 to 500 ±0.30 ±0.50																		