


Ösenlasthaken mit Schmiedefalle




- **Robuste Ausführung**
Rot lackiertes Metall.
- **Geprüfte Sicherheit**
H-Stempel, Güteklasse 8.

für Kette Ø mm	Maß A mm	Maß A2 mm	Maß D mm	Maß G mm	Maß H mm	Maß O mm	Maß R mm	Gewicht kg	Tragfähigkeit kg	€	Bestell-Nr.
6	25,0	20,5	8,5	14,5	20	20,5	80,5	0,27	1120	13,05	3060 2010
7/8	29,5	24,5	11,0	19,0	27	25,0	95,5	0,50	2000	19,30	3060 2011
10	35,7	29,0	14,0	23,5	33	34,0	120,5	0,90	3150	33,80	3060 2012
13	43,5	35,4	17,5	29,0	40	42,5	150,0	1,50	5300	56,70	3060 2013
16	52,5	44,0	22,0	35,5	49	52,0	183,0	2,75	8000	98,10	3060 2014
20	60,0	52,0	27,0	48,0	53	55,0	203,0	4,50	12500	165,00	3060 2015
22	70,0	62,0	30,0	51,5	60	60,0	224,0	7,10	15000	225,00	3060 2016
26	77,0	73,0	35,0	60,0	75	70,0	237,0	12,00	21200	398,00	3060 2017

(B456)

Ösenlasthaken mit Schmiedefalle GK 10




- **Robuste Ausführung**
In RAL 3022 lachsrot lackiertes Metall.
- **Geprüfte Sicherheit**
H-Stempel, Güteklasse 10.

für Kette Ø mm	Maß A mm	Maß A2 mm	Maß D mm	Maß G mm	Maß H mm	Maß O mm	Maß R mm	Gewicht kg	Tragfähigkeit kg	€	Bestell-Nr.
6	26	19	10	16	20	20,5	81	0,25	1400	16,65	3060 2351
7/8	33	26	11	19	29	25	101	0,50	2500	22,10	3060 2352
10	40	31	16	26	33	34	131	0,97	4000	34,60	3060 2353
13	51	40	19	33	42	43	159	1,90	6700	61,70	3060 2354
16	66	45	24,5	40	50	50	183	3,30	10000	107,50	3060 2355
20	60	52	27	48	53	55	203	4,50	16000	181,50	3060 2356
22	70	62	29	50	60	60	224	7,10	19000	254,00	3060 2357
26	77	73	35	60	75	70	257	12,00	26500	503,00	3060 2358

(B456)

Self-Locking-Haken mit Wirbel



- **Robuste Ausführung**
Rot lackiertes Metall.
- **Geprüfte Sicherheit**
H-Stempel, Güteklasse 8.

für Kette Ø mm	Maß R mm	Maß A mm	Maß B mm	Maß O mm	Maß D mm	Maß G mm	Maß H mm	Gewicht kg	Tragfähigkeit kg	€	Bestell-Nr.
6	150	28	23	33	11	15	20	0,60	1120	102,00	3060 2019
7/8	185	34	27	37	13	19	24	1,10	2000	114,50	3060 2020
10	217	45	35	42	16	23	30	2,00	3150	181,00	3060 2021
13	271	54	43	48	21	27	40	4,00	5300	245,50	3060 2022
16	334	62	58	62	22	37	49	6,80	8000	348,50	3060 2023

(B456)