## Bit für Schlitzschrauben 1/4"

**Zähhart, mit Torsionsbereich.** Ähnlich DIN 3126 C 6,3.

**642A Zähhart.** Nach DIN 3126 C 6,3


**Zähhart, mit Torsionsbereich.** Ähnlich DIN 3126 C 6,3.

				format	H Wera	₩ Wera	
Klingenbreite	Klingenstärke	Länge	VE	6421	642A	642B	Bestell-
mm	mm	mm		€	€	€	Nr.
3,0	0,5	25	10	_	0,66	_	0003
4,0	0,5	25	10	0,57	-	_	0005
4,5	0,6	25	10	-	0,66	0,92	0007
5,5	0,8	25	10	0,57	0,66	0,92	0010
5,5	1,0	25	10	0,57	-	_	0015
6,5	1,2	25	10	0,57	0,66	0,92	0020
8,0	1,2	25	10	_	1,36	_	0025
8,0	1,6	25	10	_	1,36	1,55	0030
				(W546)	(\M545)	(\\\/545)	

25 mm









## Bit für Schlitzschrauben 1/4" DIN 3126 C 6,3

Ausführung: Zähhart.

				/// Wera	
Klingenbreite	Klingenstärke	Länge	VE	6423	Bestell-
mm	mm	mm		€	Nr.
3,0	0,5	39	10	1,92	0005
3,5	0,6	39	10	1,92	0010
4,0	0,8	39	10	1,92	0015
5,5	1,0	39	10	1,92	0020
6,5	1,2	39	10	2,34	0025
8,0	1,2	39	10	2,34	0030
8,0	1,6	39	10	2,34	0035
				(W545)	





## Bit für Schlitzschrauben 1/4" DIN 3126 E 6,3

Ausführung: Zähhart.

				₩ Wera		
Klingenbreite	Klingenstärke	Länge	VE	6441	Bestell-	
mm	mm	mm		€	Nr.	
3,0	0,5	50	10	2,33	0005	
3,5	0,6	50	10	2,33	0010	
4,0	0,8	50	10	2,33	0015	
5,5	0,8	50	10	2,33	0025	
6,5	1,2	50	10	2,33	0035	
8,0	1,2	50	10	2,33	0040	
				(W545)		





## Bit für Schlitzschrauben 1/4" DIN 3126 E 6,3

Ausführung: Zähhart.

				format	₩ Wera	
Klingenbreite	Klingenstärke	Länge	VE	6467	6441	Bestell-
mm	mm	mm		€	€	Nr.
4,0	0,8	89	10	2,55	3,39	0020
5,5	1,0	89	10	2,55	3,39	0030
6,5	1,2	89	10	-	3,39	0036
8,0	1,2	89	10	_	3,39	0045
				(W546)	(W545)	



