## Zapfensenker Gr. 2





						afs	
Senk-Ø	i	Gesamt-	Kopf-	Schaft-	Boh-	1489	Bestell-
(K8) D	Schaft-Ø	länge	länge	länge	rungs-Ø		Nr.
mm	mm	mm	mm	mm	mm	€	
24	22	60	27	33	10	105,50	2400
24,5	22	60	27	33	10	105,50	2450
25	22	60	27	33	10	105,50	2500
25,5	22	60	27	33	10	105,50 ◊	2550
26	22	60	27	33	10	119,50	2600
26,5	22	60	27	33	10	119,50	2650
27	22	60	27	33	10	119,50	2700
27,5	22	60	27	33	10	119,50	2750
28	22	60	27	33	10	122,00	2800
28,5	22	60	27	33	10	122,00	2850
29	22	60	27	33	10	122,00	2900
29,5	22	60	27	33	10	122,00	2950
30	22	60	27	33	10	124,50	3000
30,5	22	60	27	33	10	124,50	3050
31	22	60	27	33	10	124,50	3100
32	22	60	27	33	10	124,50	3200
33	22	60	27	33	10	131,00	3300
34	22	60	27	33	10	131,00	3400
35	22	60	27	33	10	131,00	3500
36	22	60	27	33	10	131,00	3600
37	22	60	27	33	10	159,00	3700
38	22	60	27	33	10	159,00	3800
39	22	60	27	33	10	159,00	3900
40	22	60	27	33	10	159,00	4000
Bis Ø 85 m	nm lieferbar.					(W138)	

					_	ay 3	
Senk-Ø	i	Gesamt-	Kopf-	Schaft-	Boh-	1489	Bestell-
(K8) D	Schaft-Ø	länge	länge	länge	rungs-Ø		Nr.
mm	mm	mm	mm	mm	mm	€	
41	22	60	27	33	10	216,50	4100
42	22	60	27	33	10	216,50	4200
43	22	60	27	33	10	216,50	4300
44	22	60	27	33	10	216,50	4400
45	22	60	27	33	10	225,00	4500
46	22	60	27	33	10	225,00	4600
47	22	60	27	33	10	225,00	4700
48	22	60	27	33	10	225,00	4800
49	22	60	27	33	10	287,50 ◊	4900
50	22	60	27	33	10	286,00	5000
51	22	60	27	33	10	287,50	5100
52	22	60	27	33	10	287,50	5200
53	22	60	27	33	10	319,00	5300
54	22	60	27	33	10	319,00	5400
55	22	60	27	33	10	319,00	5500
56	22	60	27	33	10	319,00	5600
57	22	60	27	33	10	362,00 ◊	5700
58	22	60	27	33	10	362,00	5800
60	22	60	27	33	10	362,00	6000
62	22	60	27	33	10	362,00	6200
64	22	60	27	33	10	362,00 ◊	6400
65	22	60	27	33	10	362,00	6500
66	22	60	27	33	10	362,00	6600
						(W138)	

## Führungszapfen Gr. 01

Feststehend ohne Innenkühlung.



				afs	
Zapfen-Ø		Gesamt-	Kopf-	1479	Bestell-
(e8) D	Schaft-Ø	länge	länge		Nr.
mm	mm	mm	mm	€	
2,4	2,4	40	6	23,40	0240
2,5	2,4	40	6	23,40 ◊	0250
2,6	2,4	40	6	23,40 ◊	0260
2,7	2,4	40	6	23,40 ◊	0270
2,8	2,4	40	6	23,40 ◊	0280
2,9	2,4	40	6	23,40	0290
3	2,4	40	6	23,40	0300
3,1	2,4	40	6	23,40	0310
3,2	2,4	40	6	23,40	0320
3,3	2,4	40	6	23,40	0330
3,4	2,4	40	6	23,40	0340
				(W138)	

				afs	
Zapfen-Ø		Gesamt-	Kopf-	1479	Bestell-
(e8) D	Schaft-Ø	länge	länge		Nr.
mm	mm	mm	mm	€	
3,5	2,4	40	6	23,40	0350
3,6	2,4	40	6	23,40 ◊	0360
3,7	2,4	40	6	23,40 ◊	0370
3,8	2,4	40	6	23,40 ◊	0380
3,9	2,4	40	6	23,40	0390
4	2,4	40	6	23,40	0400
4,1	2,4	40	6	23,40	0410
4,2	2,4	40	6	23,40	0420
4,3	2,4	40	6	23,40 ◊	0430
4,4	2,4	40	6	23,40	0440
4,5	2,4	40	6	23,40	0450
				(W138)	

## Führungszapfen Gr. 0

Feststehend ohne Innenkühlung.



				afs	
			Kopf-	1483	Bestell-
Zapfen-Ø (e8) D	Schaft-Ø	Gesamtlänge	länge		Nr.
mm	mm	mm	mm	€	
4	4	59	9	16,15	0400
4,1	4	59	9	16,15	0410
4,2	4	59	9	16,15	0420
4,3	4	59	9	16,15 ◊	0430
4,5	4	59	9	16,15	0450
4,8	4	59	9	16,15	0480
				(W138)	

				afs	
			Kopf-	1483	Bestell-
Zapfen-Ø (e8) D	Schaft-Ø	Gesamtlänge	länge		Nr.
mm	mm	mm	mm	€	
4,9	4	59	9	16,15	0490
5	4	59	9	16,15	0500
5,3	4	59	9	16,15	0530
5,5	4	59	9	17,75	0550
5,8	4	59	9	17,75	0580
5,9	4	59	9	17,75	0590
				(W138)	

(W138) Fortsetzung nächste Seite