Cortis

Gortis

## Fräserdornring, Form A

Ausführung: Aus gehärtetem Federbandstahl, gestanzt.

			Cortis	
		Außen-	3244	Bestell-
Bohrung	Breite	Ø		Nr.
mm	mm	mm	€	
16	0,03	25	3,04	0001
16	0,05	25	2,19	0004
16	0,1	25	1,26	0007
16	0,2	25	1,26	0010
16	0,3	25	1,34	0013
16	0,5	25	1,38	0016
16	0,6	25	1,50	0019
16	1	25	2,35	0022
22	0,03	33	3,16	0025
22	0,05	33	2,45	0028
22	0,1	33	1,38	0031
22	0,2	33	1,38	0034
22	0,3	33	1,56	0037
22	0,5	33	1,82	0040
22	0,6	33	1,99	0043
			(W050)	

			Cortis	
		Außen-	3244	Bestel
Bohrung	g Breite	Ø		Nr.
mm	mm	mm	€	
22	1	33	2,82	004
27	0,03	39	3,66	004
27	0,05	39	2,87	005
27	0,1	39	1,51	005
27	0,2	39	1,70	005
27	0,3	39	1,90	006
27	0,5	39	2,21	006
27	0,6	39	2,40	006
27	1	39	3,43	007
32	0,03	45	4,56	007
32	0,05	45	3,45	007
32	0,1	45	1,82	007
32	0,2	45	2,21	008
32	0,3	45	2,43	008
32	0,5	45	2,58	008
			(W050)	

DIN

2084

А



			Cortis	
		Außen-	3244	Bestell-
Bohrung	Breite	Ø		Nr.
mm	mm	mm	€	
32	0,6	45	2,86	0091
32	1	45	4,22	0094
40	0,03	54	5,30	0097
40	0,5	54	4,15	0100
40	0,1	54	2,45	0103
40	0,2	54	2,86	0106
40	0,3	54	3,94	0109
40	0,5	54	4,05	0112
40	0,6	54	4,79	0115
40	1	54	7,25	0118
			(W050)	

## Fräserdornring, Form B

Ausführung: Aus gehärtetem Federbandstahl.

			Cortis					(
		Außen-	3244	Bestell-			Außen-	
Bohrung	g Breite	Ø		Nr.	Bohrun	g Breite	Ø	
mm	mm	mm	€		mm	mm	mm	
16	2	27	10,70	0121	22	30	34	
16	3	27	10,70	0124	27	2	41	
16	5	27	13,80	0127	27	3	41	
16	6	27	11,55	0130	27	5	41	
16	10	27	16,15	0133	27	6	41	
16	20	27	20,50	0136	27	10	41	
16	30	27	25,20	0139	27	20	41	
22	2	34	10,80	0142	27	30	41	
22	3	34	10,80	0145	32	2	47	
22	5	34	12,45	0148	32	3	47	
22	6	34	13,20	0151	32	5	47	
22	10	34	23,60	0154	32	6	47	
22	20	34	30,80	0157	32	10	47	
			(W050)					



...0175

...0178 ...0181

...0184

...0187

...0190 ...0193

...0196

20,00 25,90

36,80

12,80 14,95

16,40

18,05 23,60

(W050)

В

DIN

2084



			Cortis	
		Außen-	3244	Bestell-
Bohrung	Breite	Ø		Nr.
mm	mm	mm	€	
32	20	47	32,80	0199
32	30	47	40,10	0202
40	2	55	16,15	0205
40	3	55	17,40	0208
40	5	55	21,20	0211
40	6	55	23,10	0214
40	10	55	29,80	0217
40	20	55	43,00	0220
40	30	55	49,80	0223
			(W050)	

4

3

2

## Fräserdornring-Satz

Ausführung: Federbandstahl, gehärtet.										DIN 2084	А						Ģ	ortís
Daha			Gortis	Deste	11						0				2		-	
Bohr	•		3247	Beste	-11							-		-		-		
mr		<u> </u>	€	Nr.					-	-	and the second second	- 6	61	30				
16		0	116,00	00									and the second	-				
22	35-te	lig	126,00	00	04				States of the local division of the local di	100	-				- 1		-	Contraction of the local division of the loc
27	35-tei	ilig	136,50	00	07										-		Constant State	
32	35-te	ilig	155,00	00	10				Gort	is							1	
40	35-tei	lig	207,00	00	13	Bohru	ing		324	7	Bestell-							
16	35-te	ilig	143,00	00	16	mm	1	Ausführung	€		Nr.							
22	60-te	lig	174,00	00	19	32		60-teilig	240,0	) .	0025							
27	60-te	ilig	207,00	00	22	40		60-teilig	267,0	) .	0028							
			(W050)						(W05	C)								
Sortiment 35 Stück									Sortime	nt 60 S	Stück							
Inhalt –	Ringbreite mm	/Stüc	k						Inhalt –	Ringbre	eite mm/S	Stück						
0,03	0,04 0,05	C	,1 0,2	0,3	0,5	0,6	1	1,5	0,03	0,04	0,05	0,1	0,2	0,3	0,5	0,6	1	1,5

Sortiment 35 Stück											Sortiment 60 Stück								
Inhalt – Ringbreite mm/Stück									Inhalt – Ringbreite mm/Stück										
0,03	0,04	0,05	0,1	0,2	0,3	0,5	0,6	1	1,5	0,03	0,04	0,05	0,1	0,2	0,3				
5	5	5	6	3	3	3	2	2	1	10	10	10	10	5	5				

1