
## Werkzeug-Rundbürste

Ausführung: Mit 6-mm-Schaft.





## Stahldraht, gewellt



								format professional quality	LESSM/\NN°	
	Arbeitsbreite min.		Besatzlänge		Drahtstärke			7024	7978	Bestell- Nr.
Bürsten-Ø	mm		mm		mm		max. Drehzahl			
mm	7024	7978	7024	7978	7024	7978	min <sup>-1</sup>	€	€	
30	9	6	6	6	0,2	0,2	20000	3,87	5,95	0030
40	11	9	10	9	0,2	0,2	18000	4,16	5,40	0040
50	17	_	13	_	0,2	_	15000	5,10	_	0050
50	_	11	-	12	_	0,3	15000	_	6,35	0051
60	_	18	-	17	_	0,3	15000	_	8,50	0061
60	18	_	15	_	0,3	_	15000	5,90	_	0061
70	_	13	-	19	_	0,3	15000	_	8,75	0071
70	18	-	15	-	0,3	_	15000	6,15	_	0071
80	19	_	20	_	0,3	_	12000	6,35	_	0080
								(W566)	(W872)	

## Rostfreier Stahldraht, gewellt







7026 **format** 

7979 + 7980 LESSMANN

								format professional quality	LESSM/NN"	LESSM/NN <sup>®</sup>	
	۸rhoi	tobroito mi	n	Poo	atzlänga			7026	7979	7980	Bestell-
Bürsten-Ø	Arbeitsbreite min. mm			Besatzlänge mm		Drahtstärke	max. Drehzahl	V2A	V2A	V4A	Nr.
mm	7026	7979	7980	7026	7979/7980	mm	min <sup>-1</sup>	€	€	€	
30	9	6	_	6	6	0,2	20000	4,91	7,70	_	0030
40	11	9	_	10	9	0,2	18000	6,10	8,40	_	0040
50	17	11	11	13	12	0,2	15000	7,95	10,30	15,60	0050
50	_	11	_	_	12	0,3	15000	_	8,80	_	0051
60	18	_	_	15	_	0,2	15000	8,95	_	_	0060
60	_	18	_	_	17	0,3	15000	_	11,55	_	0061
70	18	13	_	15	19	0,2	15000	9,80	13,95	_	0070
70	_	13	9	_	19	0,3	15000	_	12,10	16,55	0071
								(W566)	(W872)	(W875)	

## Messingdraht, gewellt

					format	
Bürsten-Ø A	Arbeitsbreite min.	Besatzlänge	Drahtstärke	max. Drehzahl	7028	Bestell-
mm	mm	mm	mm	min <sup>-1</sup>	€	Nr.
30	9	6	0,2	20000	5,45	0030
40	11	10	0,2	18000	6,35	0040
50	17	13	0,2	15000	8,30	0050
60	18	15	0,2	15000	9,50	0060
70	18	15	0,2	15000	10,05	0070
					(W566)	





