


Einschraubschlauchtülle mit Außengewinde

Ausführung: Aus Messing.

Anschluss Zoll	Schlauchanschluss mm	SW mm	Betriebsdruck bar	Betriebstemperatur °C	RIEGLER	Bestell- Nr.
					9416	
					€	
G 1/8	6	14	25	150	1,41	...0590
G 1/4	6	17	25	150	1,65	...0595
G 3/8	6	19	25	150	1,77	...0600
G 1/4	9	17	25	150	1,65	...0605
G 3/8	9	19	25	150	1,86	...0610
G 1/2	9	24	25	150	2,88	...0615
G 3/8	13	19	25	150	2,16	...0620
G 1/2	13	24	25	150	3,03	...0625
G 3/4	13	32	25	150	6,20	...0630
G 3/4	16	32	25	150	6,20	...0635
G 3/4	19	32	25	150	5,60	...0640

(W971)



Doppelschlauchtülle

Ausführung: Aus Messing.

Schlauch-Innen-Ø mm	Länge mm	Betriebsdruck bar	Mediumstemperatur °C	RIEGLER	Bestell- Nr.
				9416	
				€	
6	55	16	90	1,59	...0646
9	55	16	90	1,87	...0651
13	55	16	90	2,65	...0656

(W971)



Doppelnippel mit Außengewinde

Ausführung: Aus Messing.

Anschluss Zoll	SW mm	Betriebsdruck bar	Betriebstemperatur °C	RIEGLER	Bestell- Nr.
				9416	
				€	
G 1/8 x G 1/8	14	25	150	0,88	...0660
G 1/4 x G 1/4	17	25	150	1,04	...0665
G 3/8 x G 3/8	19	25	150	1,22	...0670
G 1/2 x G 1/2	24	25	150	2,24	...0675
G 3/4 x G 3/4	32	25	150	4,99	...0680
G 1/8 x G 1/4	17	25	150	1,14	...0685
G 1/4 x G 3/8	19	25	150	1,38	...0690
G 3/8 x G 1/2	24	25	150	2,50	...0695
G 1/2 x G 3/4	32	25	150	3,02	...0700

(W971)



Muffe mit Innengewinde

Ausführung: Aus Messing mit durchgängigem Gewinde.

Anschluss Zoll	SW mm	Betriebsdruck bar	Betriebstemperatur °C	RIEGLER	Bestell- Nr.
				9416	
				€	
G 1/8	14	25	150	1,20	...0711
G 1/4	17	25	150	1,53	...0716
G 3/8	22	25	150	2,16	...0721
G 1/2	27	25	150	3,33	...0726
G 3/4	32	25	150	5,85	...0731

(W971)



T-Stück

Ausführung: Aus Messing, mit Außen- (AG) und Innengewinde (IG). Das Innengewinde ist zylindrisch nach DIN EN ISO 228-1 und das Außengewinde konisch nach DIN 2999.

9416 0735 Mit Außengewinde.
- 0745

Anschluss Zoll	SW mm	Betriebsdruck bar	Betriebstemperatur °C	RIEGLER	Bestell- Nr.
				9416	
				€	
R 1/4	13	60	150	3,75	...0735
R 3/8	17	60	150	5,55	...0740
R 1/2	21	60	150	8,05	...0745

(W971)



9416 0735-0745

9416 0750 Mit Innengewinde.
- 0760

Anschluss Zoll	SW mm	Betriebsdruck bar	Betriebstemperatur °C	RIEGLER	Bestell- Nr.
				9416	
				€	
G 1/4	13	60	150	4,34	...0750
G 3/8	17	60	150	6,05	...0755
G 1/2	21	60	150	8,10	...0760

(W971)



9416 0750-0760

