


## Ösenlasthaken mit Schmiedefalle

- **Robuste Ausführung**  
Rot lackiertes Metall.
- **Geprüfte Sicherheit**  
H-Stempel, Güteklasse 8.




| für Kette Ø<br>mm | Maß A<br>mm | Maß A2<br>mm | Maß D<br>mm | Maß G<br>mm | Maß H<br>mm | Maß O<br>mm | Maß R<br>mm | Gewicht<br>kg | Tragfähigkeit<br>kg | €      | Bestell-Nr. |
|-------------------|-------------|--------------|-------------|-------------|-------------|-------------|-------------|---------------|---------------------|--------|-------------|
| 6                 | 25,0        | 20,5         | 8,5         | 14,5        | 20          | 20,5        | 80,5        | 0,27          | 1120                | 12,50  | 3060 2010   |
| 7/8               | 29,5        | 24,5         | 11,0        | 19,0        | 27          | 25,0        | 95,5        | 0,50          | 2000                | 18,90  | 3060 2011   |
| 10                | 35,7        | 29,0         | 14,0        | 23,5        | 33          | 34,0        | 120,5       | 0,90          | 3150                | 32,40  | 3060 2012   |
| 13                | 43,5        | 35,4         | 17,5        | 29,0        | 40          | 42,5        | 150,0       | 1,50          | 5300                | 55,40  | 3060 2013   |
| 16                | 52,5        | 44,0         | 22,0        | 35,5        | 49          | 52,0        | 183,0       | 2,75          | 8000                | 95,90  | 3060 2014   |
| 20                | 60,0        | 52,0         | 27,0        | 48,0        | 53          | 55,0        | 203,0       | 4,50          | 12500               | 161,50 | 3060 2015   |
| 22                | 70,0        | 62,0         | 30,0        | 51,5        | 60          | 60,0        | 224,0       | 7,10          | 15000               | 220,00 | 3060 2016   |
| 26                | 77,0        | 73,0         | 35,0        | 60,0        | 75          | 70,0        | 237,0       | 12,00         | 21200               | 389,50 | 3060 2017   |

(B456)

## Ösenlasthaken mit Schmiedefalle GK 10

- **Robuste Ausführung**  
In RAL 3022 lachsrot lackiertes Metall.
- **Geprüfte Sicherheit**  
H-Stempel, Güteklasse 10.




| für Kette Ø<br>mm | Maß A<br>mm | Maß A2<br>mm | Maß D<br>mm | Maß G<br>mm | Maß H<br>mm | Maß O<br>mm | Maß R<br>mm | Gewicht<br>kg | Tragfähigkeit<br>kg | €      | Bestell-Nr. |
|-------------------|-------------|--------------|-------------|-------------|-------------|-------------|-------------|---------------|---------------------|--------|-------------|
| 6                 | 26          | 19           | 10          | 16          | 20          | 20,5        | 81          | 0,25          | 1400                | 16,30  | 3060 2351   |
| 7/8               | 33          | 26           | 11          | 19          | 29          | 25          | 101         | 0,50          | 2500                | 21,60  | 3060 2352   |
| 10                | 40          | 31           | 16          | 26          | 33          | 34          | 131         | 0,97          | 4000                | 33,80  | 3060 2353   |
| 13                | 51          | 40           | 19          | 33          | 42          | 43          | 159         | 1,90          | 6700                | 60,30  | 3060 2354   |
| 16                | 66          | 45           | 24,5        | 40          | 50          | 50          | 183         | 3,30          | 10000               | 105,00 | 3060 2355   |
| 20                | 60          | 52           | 27          | 48          | 53          | 55          | 203         | 4,50          | 16000               | 177,50 | 3060 2356   |
| 22                | 70          | 62           | 29          | 50          | 60          | 60          | 224         | 7,10          | 19000               | 248,50 | 3060 2357   |
| 26                | 77          | 73           | 35          | 60          | 75          | 70          | 257         | 12,00         | 26500               | 491,50 | 3060 2358   |

(B456)

## Self-Locking-Haken mit Wirbel

- **Robuste Ausführung**  
Rot lackiertes Metall.
- **Geprüfte Sicherheit**  
H-Stempel, Güteklasse 8.



| für Kette Ø<br>mm | Maß R<br>mm | Maß A<br>mm | Maß B<br>mm | Maß O<br>mm | Maß D<br>mm | Maß G<br>mm | Maß H<br>mm | Gewicht<br>kg | Tragfähigkeit<br>kg | €      | Bestell-Nr. |
|-------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|---------------|---------------------|--------|-------------|
| 6                 | 150         | 28          | 23          | 33          | 11          | 15          | 20          | 0,60          | 1120                | 99,90  | 3060 2019   |
| 7/8               | 185         | 34          | 27          | 37          | 13          | 19          | 24          | 1,10          | 2000                | 112,00 | 3060 2020   |
| 10                | 217         | 45          | 35          | 42          | 16          | 23          | 30          | 2,00          | 3150                | 177,00 | 3060 2021   |
| 13                | 271         | 54          | 43          | 48          | 21          | 27          | 40          | 4,00          | 5300                | 240,00 | 3060 2022   |
| 16                | 334         | 62          | 58          | 62          | 22          | 37          | 49          | 6,80          | 8000                | 340,50 | 3060 2023   |

(B456)