

WEMAG Spiralbohrer HSS DIN 340 blank

Werkzeugdaten



Einsatzmöglichkeiten



Stahl			INOX		Guss		Sonder-Legierung		NE-Metalle						Gehärteter Stahl		
< 700 N/mm ²	< 1.000 N/mm ²	< 1.400 N/mm ²	< 700 N/mm ²	> 700 N/mm ²	GG/GTS	GGG	Inconel, Hastelloy, Nimonic	Titan	Alu lang	Alu kurz	Alu > 8% Si	Kupfer, Messing, Bronze	Kunststoff, Thermoplaste	Graphit/ GFK/CFK	< 55 HRC	< 60 HRC	> 60 HRC
22	18				25	15			vc = m/min.		45						

Artikelnr.	d1	L1	L2	f mm/U	VE	Preis
1005577.0100	1	56	33	0,014 – 0,018	10	0,80
1005577.0150	1,5	70	45	0,014 – 0,018	10	0,96
1005577.0200	2	85	56	0,040 – 0,063	10	1,15
1005577.0250	2,5	95	62	0,050 – 0,080	10	1,15
1005577.0300	3	100	66	0,050 – 0,080	10	1,34
1005577.0310	3,1	106	69	0,050 – 0,080	10	1,63
1005577.0320	3,2	106	69	0,063 – 0,100	10	1,63
1005577.0330	3,3	106	69	0,063 – 0,100	10	1,73
1005577.0350	3,5	112	73	0,063 – 0,100	10	1,63
1005577.0400	4	119	78	0,080 – 0,125	10	1,73
1005577.0410	4,1	119	78	0,080 – 0,125	10	2,30
1005577.0420	4,2	119	78	0,080 – 0,125	10	2,30
1005577.0450	4,5	126	82	0,080 – 0,125	10	2,11
1005577.0500	5	132	87	0,080 – 0,125	10	2,50
1005577.0510	5,1	132	87	0,080 – 0,125	10	3,26
1005577.0520	5,2	132	87	0,080 – 0,125	10	3,26
1005577.0550	5,5	139	91	0,080 – 0,125	10	3,07
1005577.0580	5,8	139	91	0,080 – 0,125	10	3,69
1005577.0600	6	139	91	0,080 – 0,125	5	3,65
1005577.0650	6,5	148	97	0,100 – 0,160	5	4,05
1005577.0680	6,8	156	102	0,100 – 0,160	5	5,86
1005577.0700	7	156	102	0,100 – 0,160	5	4,68
1005577.0750	7,5	156	102	0,100 – 0,160	5	5,31
1005577.0800	8	165	109	0,125 – 0,200	5	6,03
1005577.0850	8,5	165	109	0,125 – 0,200	5	6,48
1005577.0900	9	175	115	0,125 – 0,200	5	7,06
1005577.0950	9,5	175	115	0,125 – 0,200	5	8,28
1005577.1000	10	184	121	0,160 – 0,250	5	8,99
1005577.1020	10,2	184	121	0,160 – 0,250	5	11,50
1005577.1050	10,5	184	121	0,160 – 0,250	5	11,50
1005577.1100	11	195	128	0,160 – 0,250	5	12,35
1005577.1150	11,5	195	128	0,160 – 0,250	5	13,65
1005577.1200	12	205	134	0,160 – 0,250	5	15,20
1005577.1250	12,5	205	134	0,160 – 0,250	5	15,45
1005577.1300	13	205	134	0,160 – 0,250	5	16,15

(1015)