

Zapfensenker Gr. 2

HSS



1.4

Senk-Ø (K8) D		Schaft-Ø	Gesamt- länge	Kopf- länge	Schaft- länge	Boh- rungs-Ø	1489	Bestell- Nr.
mm	mm	mm	mm	mm	mm	mm	€	
24	22	60	27	33	10	107,50	...2400	
24,5	22	60	27	33	10	107,50	...2450	
25	22	60	27	33	10	107,50	...2500	
25,5	22	60	27	33	10	107,50	...2550	
26	22	60	27	33	10	122,00	...2600	
26,5	22	60	27	33	10	122,00	...2650	
27	22	60	27	33	10	122,00	...2700	
27,5	22	60	27	33	10	122,00	...2750	
28	22	60	27	33	10	124,00	...2800	
28,5	22	60	27	33	10	124,00	...2850	
29	22	60	27	33	10	124,00	...2900	
29,5	22	60	27	33	10	124,00	...2950	
30	22	60	27	33	10	127,00	...3000	
31	22	60	27	33	10	127,00	...3100	
32	22	60	27	33	10	127,00	...3200	
33	22	60	27	33	10	133,00	...3300	
34	22	60	27	33	10	133,00	...3400	
35	22	60	27	33	10	133,00	...3500	
36	22	60	27	33	10	133,00	...3600	
37	22	60	27	33	10	162,00	...3700	
38	22	60	27	33	10	162,00	...3800	
39	22	60	27	33	10	162,00	...3900	

Bis Ø 85 mm lieferbar.

(W138)

Senk-Ø (K8) D		Schaft-Ø	Gesamt- länge	Kopf- länge	Schaft- länge	Boh- rungs-Ø	1489	Bestell- Nr.
mm	mm	mm	mm	mm	mm	mm	€	
40	22	60	27	33	10	162,00	...4000	
41	22	60	27	33	10	220,50	...4100	
42	22	60	27	33	10	220,50	...4200	
43	22	60	27	33	10	220,50	...4300	
44	22	60	27	33	10	220,50	...4400	
45	22	60	27	33	10	229,00	...4500	
46	22	60	27	33	10	229,00	...4600	
47	22	60	27	33	10	229,00	...4700	
48	22	60	27	33	10	229,00	...4800	
49	22	60	27	33	10	292,50	...4900	
50	22	60	27	33	10	291,00	...5000	
52	22	60	27	33	10	292,50	...5200	
53	22	60	27	33	10	325,00	...5300	
54	22	60	27	33	10	325,00	...5400	
55	22	60	27	33	10	325,00	...5500	
56	22	60	27	33	10	325,00	...5600	
58	22	60	27	33	10	368,50	...5800	
60	22	60	27	33	10	368,50	...6000	
62	22	60	27	33	10	368,50	...6200	
64	22	60	27	33	10	368,50	...6400	
65	22	60	27	33	10	368,50	...6500	
66	22	60	27	33	10	368,50	...6600	

(W138)

Führungszapfen Gr. 01

Feststehend ohne Innenkühlung.



Zapfen-Ø (e8) D		Schaft-Ø	Gesamtlänge	Kopflänge	1479	Bestell- Nr.
mm	mm	mm	mm	mm	€	
2,4	2,4	40	6	23,70	...0240	
2,5	2,4	40	6	23,70	...0250	
2,6	2,4	40	6	23,70	...0260	
2,7	2,4	40	6	23,70	...0270	
2,8	2,4	40	6	23,70	...0280	
2,9	2,4	40	6	23,70	...0290	
3	2,4	40	6	23,70	...0300	
3,1	2,4	40	6	23,70	...0310	
3,2	2,4	40	6	23,70	...0320	
3,3	2,4	40	6	23,70	...0330	
3,4	2,4	40	6	23,70	...0340	

(W138)

Zapfen-Ø (e8) D		Schaft-Ø	Gesamtlänge	Kopflänge	1479	Bestell- Nr.
mm	mm	mm	mm	mm	€	
3,5	2,4	40	6	23,70	...0350	
3,6	2,4	40	6	23,70	...0360	
3,7	2,4	40	6	23,70	...0370	
3,8	2,4	40	6	23,70	...0380	
3,9	2,4	40	6	23,70	...0390	
4	2,4	40	6	23,70	...0400	
4,1	2,4	40	6	23,70	...0410	
4,2	2,4	40	6	23,70	...0420	
4,3	2,4	40	6	23,70	...0430	
4,4	2,4	40	6	23,70	...0440	
4,5	2,4	40	6	23,70	...0450	

(W138)

Führungszapfen Gr. 0

Feststehend ohne Innenkühlung.



Zapfen-Ø (e8) D		Schaft-Ø	Gesamtlänge	Kopflänge	1483	Bestell- Nr.
mm	mm	mm	mm	mm	€	
4	4	59	9	16,45	...0400	
4,1	4	59	9	16,45	...0410	
4,2	4	59	9	16,45	...0420	
4,3	4	59	9	16,45	...0430	
4,5	4	59	9	16,45	...0450	
4,8	4	59	9	16,45	...0480	
4,9	4	59	9	16,45	...0490	

(W138)

Zapfen-Ø (e8) D		Schaft-Ø	Gesamtlänge	Kopflänge	1483	Bestell- Nr.
mm	mm	mm	mm	mm	€	
5	4	59	9	16,45	...0500	
5,3	4	59	9	16,45	...0530	
5,5	4	59	9	18,00	...0550	
5,8	4	59	9	18,00	...0580	
5,9	4	59	9	18,00	...0590	
6	4	59	9	18,00	...0600	
6,1	4	59	9	18,00	...0610	

(W138)

Fortsetzung nächste Seite