

Kegelpfanne


Ausführung: Einsatzgehärtet. Für Schraubenfestigkeit entsprechend 8.8 geeignet.

Anwendung: Nur für ebene, geschlossene Ringflächen.

Hinweis: Für Langlöcher nicht zulässig.

DIN
6319 D

CAD-Daten



Größe	max. Schraubkraft kN	Bohrungs-Ø D2 mm	Außen-Ø D4 mm	Höhe H3 mm	AMF 3911 €	Bestell- Nr.
M8	17	9,6	17	3,5	0,53	...0110
M10	26	12	21	4,2	0,76	...0120
M12	38	14,2	24	5	0,85	...0130
M14	53	16,5	28	5,6	1,54	...0140
M16	73	19	30	6,2	1,64	...0150
M20	117	23,2	36	7,5	2,52	...0160
M24	168	28	44	9,5	4,14	...0170

(W342)


Kegelpfanne

Ausführung: Stahl, vergütet auf 350 + 80 HV30.

Anwendung: Besonders geeignet zum Spannen über den Schlitz bei Spanneisen und Langlöchern.

DIN
6319 G

CAD-Daten



für Schrauben metrisch	Bohrungs-Ø D2 mm	Außen-Ø D4 mm	Höhe H3 mm	AMF 3912 €	Bestell- Nr.
M8	9,6	24	5	1,26	...0110
M10	12	30	5	1,26	...0120
M12	14,2	36	6	1,59	...0130
M14	16,5	40	6	2,40	...0140
M16	19	44	7	2,40	...0150
M20	23,2	50	8	3,38	...0160
M24	28	60	10	5,70	...0170

(W342)

Spannpratze, kurz, stufenlos verstellbar


NEU

Ausführung: Spannpratze aus Stahl, geschmiedet, vergütet und verzinkt.

Lieferumfang: Spannpratze mit Schraube für T-Nuten DIN 787, Sechskantmutter DIN 6330-B und Unterlegscheibe DIN 6340.



CAD-Daten



Nutenbreite mm	B1 mm	T-Nutenschraube	Spannhöhe H1 mm	B2 x L mm	D mm	E1 mm	E2 mm	H2 mm	K mm	AMF 3676 €	Bestell- Nr.
12	13	M12 x 12 x 100	0-35	38 x 88	52	23	27	30- 55	14	40,40	...0012
14	13	M12 x 14 x 100	0-35	38 x 88	52	23	27	30- 55	14	41,00	...0014
16	18	M16 x 16 x 160	0-55	56 x 130	79	29	37	42- 84	18	52,60	...0016
18	18	M16 x 18 x 160	0-55	56 x 130	79	29	37	42- 84	18	52,60	...0018
20	22	M20 x 20 x 200	0-65	66 x 144	84	32	42	50-100	20	72,40	...0020

(W342)