

Spannzange, System ER

Fortsetzung

ER25/430E Ø	D	L	fortis 3141	Bestell-Nr.
mm	mm	mm	€	
2	26	34	21,30	...0001
3	26	34	16,40	...0004
4	26	34	16,40	...0007
5	26	34	16,40	...0010
6	26	34	16,40	...0013
7	26	34	16,40	...0016
8	26	34	16,40	...0019
9	26	34	16,40	...0022
10	26	34	16,40	...0025
11	26	34	16,40	...0028
12	26	34	16,40	...0031
13	26	34	16,40	...0034
14	26	34	16,40	...0037
15	26	34	16,40	...0040
16	26	34	16,40	...0043

(W054)

ER32/470E Ø	D	L	fortis 3143	Bestell-Nr.
mm	mm	mm	€	
3	33	40	17,15	...0001
4	33	40	17,15	...0004
5	33	40	17,15	...0007
6	33	40	17,15	...0010
7	33	40	17,15	...0013
8	33	40	17,15	...0016
9	33	40	17,15	...0019
10	33	40	17,15	...0022
11	33	40	17,15	...0025
12	33	40	17,15	...0028
13	33	40	17,15	...0031
14	33	40	17,15	...0034
15	33	40	17,15	...0037

(W054)

Spannzangensatz mit Holzsockel

Spannbereich mm	Spannzangen Typ	Inhalt	fortis 3144	Bestell-Nr.
			€	
1-7	ER11/4008E	13-teilig	159,50	...0200
1-10	ER16/426E	10-teilig	145,50	...0300
2-13	ER20/428E	12-teilig	212,00	...0400
2-16	ER25/430E	15-teilig	239,00	...0500
3-20	ER32/470E	18-teilig	309,50	...0600
4-26	ER40/472E	23-teilig	475,00	...0700

(W054)

DIN
6499 B


Spannzange, System ER

Ausführung: Doppelt geschlitzt. System ER, Rundlaufgenauigkeit 0,005 mm. Eine Walkbewegung der Fräser ist ausgeschlossen, dadurch hohe Präzision bei der Zerspanung und lange Standzeit.

Anwendung: Mehrbereichs-Spannzange ab Ø 2 mm zum Spannen bis max. 1 mm unter Nenndurchmesser (ER11 0,5 mm).

ER11/4008E Ø	D	L	format 3520	Bestell-Nr.
mm	mm	mm	€	
1	11,5	18	21,50	...0001
1,5	11,5	18	21,50	...0004
2	11,5	18	21,50	...0007
2,5	11,5	18	18,65	...0010
3	11,5	18	18,65	...0013
3,5	11,5	18	18,65	...0016
4	11,5	18	18,65	...0019
4,5	11,5	18	18,65	...0022
5	11,5	18	18,65	...0025
5,5	11,5	18	18,65	...0028

(W320)

DIN
6499 B
format
professional quality


ER11/4008E Ø	D	L	format 3520	Bestell-Nr.
mm	mm	mm	€	
6	11,5	18	18,65	...0031
6,5	11,5	18	18,65	...0034
7	11,5	18	18,65	...0037

(W320)

Fortsetzung nächste Seite